

## TECHNICAL DATA SHEET

Appearance: Satin

Composition: Mixture of acrylic resins, pigments, additives and fillers

Brookfield Viscosity: 8,000 CPS

Water Vapor Permeability: Very good

Alkali Resistance: Resistant

Dry Matter: 20%

AMUR Metallic / Classic

Amur is a water-based acrylic paint for interior and exterior wall surfaces, based on special metallic or pastel pigments, offering a decorative appearance and a wide range of application techniques.

### Surface Preparation:

When the wall is prepared and ready for painting, apply 1–2 coats of Diffany as a base in the desired shade, diluted with 40–50% water. The base coat can be any shade from the FashionPaint range depending on the desired final effect. After 6 to 8 hours, when the base coat is dry, begin applying AMUR.

### Application:

Apply AMUR using a standard roller. For various decorative techniques, use a decorative roller, decorative brush, PVC trowel, or plastic foil. After applying AMUR, you have 10 to 15 minutes to create decorative effects.

For heavily loaded wall surfaces (stairs, hallways, kindergartens), we recommend applying at least one coat of BB Soft varnish (matte or gloss depending on the desired finish).

Consumption: 12–16 m<sup>2</sup>

Dilution: up to 20% with water

Drying: 6 to 8 hours / fully dry and washable after 16–24 hours

Application temperature: +5°C to +35°C.

Clean tools with water after use.

Storage: Store in dry and ventilated areas at temperatures between +5°C and +25°C. Do not freeze!

These instructions are based on our best experience. However, due to the wide variety of users and application techniques, we cannot guarantee results in every individual case.

