

APPEARANCE: Satin

COMPOSITION:

Mixture of acrylic resins, pigments, additives without fillers

VISCOSITY (FORD 4, 20°C):

20 ± 2 seconds

WATER VAPOR PERMEABILITY:

Good

ALKALI RESISTANCE:

Resistant

DRY MATTER:

+25%

These instructions are based on our best experience. However, due to the wide range of users and application techniques, we cannot guarantee results in every case.

AQUA BLOCK LAZURA

LAZURA is a water-based wood coating that protects wood while preserving its natural structure. It is made from acrylic binders, wax, and weather-resistant pigments. Suitable for both interior and exterior wood protection.

It provides excellent protection against weather conditions, UV rays, moisture, and decay. Aqua Block Lazura enhances the appearance of wood, penetrates deeply, protects it, emphasizes its structure, and gives it a silky sheen.

Unlike traditional solvent-based stains, Aqua Block Lazura is more environmentally friendly, dries faster, and has no unpleasant odor.

Surface preparation:

The wood must be properly dry (max. 20% moisture), sanded, degreased, and cleaned of dust. Use protective equipment (clothing, gloves, etc.). The wood should be properly treated (no water retention on surfaces, edges should not be sharp).

For new wood protection, we recommend applying three coats.

Application:

Apply with a brush, spray, or roller. Can be diluted with water or a special slow thinner up to 10% to delay drying.

Apply in two or three coats with intervals of 3 to 4 hours.

Drying time:

Surface: 3 to 4 hours

Fully dry: 6 to 12 hours (depending on temperature and wood moisture)

Application temperature:

+5°C to +35°C

Relative humidity: max. 80%

Clean tools with water after use. Do not pour contaminated water into drains.

Storage:

Store in original packaging in dry and ventilated areas at temperatures between +5°C and +25°C.

Advantages:

- Easy tool cleaning
- Fast drying
- Silky or velvety appearance
- Transparent film
- Alkali resistant
- Water repellent
- Deep penetration into wood
- UV stable
- Fresh smell
- Environmentally friendly product

Consumption:

16–20 m² per liter per coat

Dilution:

Up to 10% with water

Drying:

3–4 hours / fully dry after 12 hours

Application temperature:

+5°C to +35°C

Must not freeze!