

TECHNICAL DATA SHEET

Appearance: Matte

Composition: Mixture of acrylic resins, pigments and additives

Brookfield Viscosity: 7,000 CPS

Water Vapor Permeability: Good

Alkali Resistance: Resistant

Dry Matter: 22%

BETON OPTIK

Beton Optik is based on waterborne acrylic binders and pigments, creating a unique decorative appearance on TRAVERTINE surfaces. Thanks to its easy application, Beton Optik allows the creation of distinctive and stylish ambiances in various color combinations, resembling concrete or aged wall effects.

Surface Preparation:

When the Travertine decorative plaster is dry and free of dust, apply Beton Optik with a sponge or brush in one or more coats, diluted with water up to max. 30%.

Application:

Apply Beton Optik with a sponge in one or more coats. It can be tinted with mixing pigments depending on the desired final appearance. Interval between coats: 2 to 3 hours.

Consumption: 12–16 m²/L

Dilution: up to 30% with water or WB thinner

Drying: 6 to 12 hours depending on temperature and humidity

Application temperature: +5°C to +35°C. Relative humidity max. 80%.

Clean tools with water after use. Do not pour contaminated water into drains.

Storage: Store in dry and ventilated areas between +5°C and +25°C. Do not freeze!

These instructions are based on our best experience. However, due to the wide variety of users and application techniques, we cannot guarantee results in every individual case.