



Technical Data Sheet

Appearance	Matt
Composition	Selected vinyl-siloxane resins, fillers and pigments
BROOKFIELD viscosity	16,000 CPS
Water vapour permeability	High
Alkali resistance	Resistant
Dry solids	62%
White point	90



DIFFANY

Vinyl-siloxane super-washable water-based matt paint with extremely high coverage, excellent application properties and weather resistance, suitable for interior and exterior surfaces, with a pleasant fragrance. A paint that breathes. DIFFANY paint is ideal for painting plaster, plasterboard, filled and mineral substrates. Its formula has been developed using the latest technologies of the modern chemical industry and complies with all provisions of the European Directive.

Application:

On the surface, we recommend first applying 1 coat of acrylic emulsion. For basements or rooms with high humidity, do not use emulsion! We recommend two coats of 'DIFFANY' diluted with 40 to 50% water. The same procedure is also recommended for exterior use.

Packaging: 0.750 L - 2.5 L - 5 L - 14 L

Properties:

Consumption: 14 to 18 m² / L
Drying time: 4-6 hours; washable after 72 hours
Thinner: Water 40 to 50%

Application:

Brush, roller, spray gun. Time between coats: 4 to 6 hours.

Surface preparation: Remove dirt and old loose paint.