

TECHNICAL DATA SHEET

FASADIL – ACRYLIC RENDER

SCRATCHED (R) / SMOOTH (K)

Purpose:

Fasadil is a paste-like acrylic render intended for protection and decoration of exterior and interior wall surfaces. It is applied on substrates such as ETICS adhesive layers, plaster, or other similar materials.

Surface Preparation:

The surface must be solid, flat, dry, clean, and free of dust and grease. Before application, it is necessary to apply Fasadil – Grund, a structural acrylic primer in the color of the final render. After drying, Fasadil – Acrylic Render is applied.

Application Instructions:

Mix the contents thoroughly using an electric mixer. Apply the render using a stainless steel trowel in a thickness approximately 30% greater than the maximum grain size. While still workable, finish the surface by scratching or smoothing with a metal or plastic trowel to achieve the desired uniform texture.

Warning:

Application must be carried out at temperatures between +5°C and +25°C. Avoid application during rain, direct sunlight, or strong wind to prevent rapid drying.

Shelf Life:

12 months from production date. Store in original, sealed, and undamaged packaging, protected from sun and frost.

Technical Data:

Smooth Structure (K):

Grain size 1.0 mm – Consumption approx. 1.5–2.0 kg/m²

Grain size 1.5 mm – Consumption approx. 2.0–2.5 kg/m²

Grain size 2.0 mm – Consumption approx. 3.0–3.5 kg/m²

Scratched Structure (R):

Grain size 1.5 mm – Consumption approx. 2.0 kg/m²

Grain size 2.0 mm – Consumption approx. 2.5–3.0 kg/m²

Grain size 2.5 mm – Consumption approx. 3.0–3.5 kg/m²

Processing time:

Approx. 15 minutes

Packaging:

Plastic bucket 25 kg

These instructions are based on our best experience. However, due to different users and application methods, we cannot guarantee results in every individual case.