

TECHNICAL DATA SHEET

Appearance: 70% Gloss

Composition: Mixture of acrylic and vinyl resins, pigments

Brookfield Viscosity: 13,000 CPS

Water Vapor Permeability: Very low

Alkali Resistance: Resistant

Dry Matter: 20%

GALAXY

Galaxy is an exclusive water-based acrylic paint with shimmering pigments that create a galaxy-like effect. It is easy to apply and has a pleasant scent.

Surface Preparation:

When the wall or ceiling is ready for painting and free of defects such as cracks or holes, apply 1 to 2 coats of DIFFANY in different shades diluted with 40–50% water. After 8 hours, when DIFFANY is dry, proceed with applying GALAXY.

Application:

Apply GALAXY using a brush with a cross-coating technique for even pigment distribution, or with a roller for a more irregular effect. GALAXY dries in approximately 3 hours and becomes washable after 12 hours. Usually one coat is sufficient, maximum two coats. GALAXY can be diluted with water from 0% up to 40%, depending on the desired particle density. The catalog shows one coat on different colored bases.

Consumption: 8–10 m² (for two coats)

Application temperature: +5°C to +35°C. Relative humidity max. 75%.

Clean tools with water after use. Do not pour contaminated water into drains.

Storage: Store in dry and ventilated areas at temperatures between +5°C and +25°C. Do not freeze!

These instructions are based on our best experience. However, due to the wide variety of users and application techniques, we cannot guarantee results in every individual case.