

SATIN VARNISH

APPEARANCE:

Satin finish

COMPOSITION:

Acrylic resin-based coating with additives and pigments

DESCRIPTION:

Satin varnish is a water-based protective coating designed for wood and similar surfaces. It provides a smooth satin finish while protecting the material from environmental impacts.

It is suitable for both interior and exterior use. The coating enhances the natural look of wood while offering protection against moisture, UV rays, and wear.

SURFACE PREPARATION:

The surface must be clean, dry, and free of dust, grease, or old peeling coatings. Sanding is recommended before application.

APPLICATION:

Apply using a brush, roller, or spray. Stir well before use. If necessary, dilute with water up to 10%.

Apply in 2–3 coats with drying intervals between each layer.

DRYING TIME:

Touch dry: approx. 2–4 hours

Fully dry: 8–12 hours depending on conditions

APPLICATION CONDITIONS:

Temperature: +5°C to +35°C

Relative humidity: max. 80%

Clean tools with water immediately after use.

STORAGE:

Store in original packaging in a dry and ventilated area between +5°C and +25°C. Protect from freezing.

ADVANTAGES:

- Smooth satin finish
- Fast drying
- Water-based and environmentally friendly
- Low odor

- Good durability
- Easy application

CONSUMPTION:

Approx. 10–14 m² per liter per coat