

## GLOSS VARNISH

### APPEARANCE:

Gloss finish

### COMPOSITION:

Acrylic resin-based coating with additives and pigments

### DESCRIPTION:

Gloss varnish is a water-based protective coating designed for wood and similar surfaces. It provides a shiny, high-gloss finish while protecting the material from environmental influences.

Suitable for interior and exterior use. It enhances the natural beauty of wood while offering protection against moisture, UV radiation, and wear.

### SURFACE PREPARATION:

The surface must be clean, dry, sanded, and free of dust, grease, and old coatings.

### APPLICATION:

Apply with a brush, roller, or spray. Stir well before use. Dilute with water up to 10% if necessary.

Apply in 2–3 coats with drying intervals between coats.

### DRYING TIME:

Touch dry: 2–4 hours

Fully dry: 8–12 hours depending on conditions

### APPLICATION CONDITIONS:

Temperature: +5°C to +35°C

Relative humidity: max. 80%

Clean tools with water after use.

### STORAGE:

Store in original packaging in dry, ventilated areas at temperatures between +5°C and +25°C. Protect from freezing.

### ADVANTAGES:

- High-gloss finish
- Fast drying
- Water-based and environmentally friendly
- Low odor

- Durable coating
- Easy to apply

**CONSUMPTION:**

Approx. 10–14 m<sup>2</sup> per liter per coat