

## TECHNICAL DATA SHEET

Appearance: Satin

Composition: Mixture of acrylic resins, pigment additives and fillers

Brookfield Viscosity: 8,000 CPS

Water Vapor Permeability: Good

Alkali Resistance: Resistant

Dry Matter: 45%

### MIRAGE

Mirage is a water-based paint with glass particles and pearlescent pigment that creates a unique decorative appearance. Thanks to its easy application, Mirage enables the creation of a distinctive and stylish ambiance. Mirage is a high-quality product, vapor permeable, UV stable, and washable. The Mirage effect can be applied to various surfaces such as concrete, plastered walls, wood, gypsum boards, and other properly prepared surfaces.

#### Surface Preparation:

If the wall is ready for painting and without defects such as cracks or holes, begin by applying Diffany paint as a base. Diffany can be white or in any shade depending on the desired final color. After 6 to 8 hours, the surface is ready for applying the Mirage effect.

#### Application:

Mirage is applied with a decorative brush S.807 in one coat. If applied in two coats, the second coat should be diluted with up to 30% water. Interval between coats: 3 to 4 hours.

Consumption: 10–12 m<sup>2</sup>

Dilution: up to 30% with water

Drying: 3 to 4 hours surface dry, 16 to 24 hours fully washable

Application temperature: +5°C to +35°C. Relative humidity max. 80%.

Clean tools with water after use. Do not pour contaminated water into drains.

Storage: Store in dry and ventilated areas at temperatures between +5°C and +25°C. Do not freeze!

These instructions are based on our best experience. However, due to the wide variety of users and application techniques, we cannot guarantee results in every individual case.