



Technical Data Sheet

Appearance	Satin matt
Composition	Mixture of acrylic resins, additives and fillers
BROOKFIELD viscosity	9,000 CPS
Water vapour permeability	Good
Alkali resistance	Resistant
Dry solids	28%



NEBULA TRANSPARENT

Nebula varnish is used as the final decorative layer to protect heavily used wall surfaces that have been painted with dispersion, acrylic or decorative paints (such as hallways, kindergartens, schools, hospitals and public spaces). Thanks to its innovative formula, velvety matt appearance and alkali resistance, it can be used everywhere, including outdoors.

Advantages:

Easy to clean with non-abrasive cleaning agents - silky, velvety appearance - alkali resistance and high wash resistance - UV-stable - completely transparent - with a fresh fragrance.

Surface preparation:

When the painted wall with dispersion or decorative coating is dry, apply the varnish diluted with max. 25% water.

Varnish application:

The varnish is most often applied with a short-haired roller or with a brush in two coats, with a time interval of 4 to 6 hours. Drying time: 4 to 6 hours; through-drying: 12 to 24 hours. Maximum wash resistance is reached after 48 hours.

Consumption: 16 to 20 m² in one coat

Dilution: up to 10% with water

Drying time: 4 to 6 hours

Application temperature: +5 to +35 °C. Clean tools with water after use. Do not pour dirty water into the drain. Store in dry, ventilated rooms at a temperature between +5 °C and +25 °C. Do not freeze!