

TECHNICAL DATA SHEET

Appearance: Matte, fine structure with glitter

Composition: Acrylic binder, glass fillers, metallic pigments

Brookfield Viscosity: 12,000 CPS

Water Vapor Permeability: Good

Alkali Resistance: Resistant

Dry Matter: 50%

UV Stability: Good

PRESTIGE GLITTER

Prestige is a decorative paint based on acrylic binders and glass fillers with added glitter, creating a unique decorative effect. Thanks to its easy application, Prestige Glitter enables the creation of a distinctive and stylish ambiance. It belongs to the premium product range, is vapor permeable, UV stable, and washable. The Prestige effect can be applied to various surfaces such as concrete, plastered walls, wood, gypsum boards, and other properly prepared surfaces.

Usage: Interior surfaces

Surface Preparation:

If the wall is ready for painting without cracks or defects, start by applying Diffany white paint as a base or suitable substrate. The base for Prestige can be white or tinted in the shade of the final effect for better coverage. After 6 hours, you can start applying the Prestige Glitter effect.

Application:

Prestige is typically applied with a decorative brush S.839 in two cross coats. The first coat is diluted with 30% water, and the second up to 50%. Interval between coats: 3 to 4 hours. Drying time: surface dry 6 to 12 hours depending on temperature and humidity. Application temperature: +5°C to +35°C. Relative humidity max. 80%. Clean tools with water after use. Do not pour contaminated water into drains. Store in original packaging in dry and ventilated areas at temperatures between +5°C and +25°C. Do not freeze! VOC category and limit value: (A/a) 30 g/l. Product contains < 30 g/l VOC.

Packaging: 0.75 L – 2.5 L – 5.0 L

Consumption: 10–13 m²/L

Dilution: water 30–50%

These instructions are based on our best experience. However, due to the wide variety of users and application techniques, we cannot guarantee results in every individual case.