

## TECHNICAL DATA SHEET

Appearance: Matte

Composition: Acrylic resin, pigments, fillers, additives

Brookfield Viscosity: 500 CPS

Water Vapor Permeability: High

Alkali Resistance: Resistant

Dry Matter: 28%

## RUSTIK

Rustik is a decorative transparent water-based paint for exterior and interior use, based on special acrylic resins and fillers. It is breathable and resistant to UV rays.

### Surface Preparation:

When the wall or ceiling is ready for painting, begin with one coat of DIFFANY white diluted with 40–50% water. After 8 hours, when DIFFANY is dry, proceed with applying the Decorative Primer using a brush with cross strokes. One coat is required. The Decorative Primer is available in three different textures (coarse, medium, and fine), providing an optimal base for applying Rustik.

### Application:

After 8 to 12 hours, when the Decorative Primer is dry, begin applying Rustik. It can be applied using a brush, sponge, cloth, decorative roller, or decorative glove, depending on the technique and desired final effect.

Consumption: 24–28 m<sup>2</sup>

### Drying Time:

Dust dry: 3 to 4 hours

Through dry: 12 to 16 hours

Maximum washability after 48 hours

Application temperature: +5°C to +35°C. Relative humidity max. 80%.

Clean tools with water after use. Do not pour contaminated water into drains.

Storage: Store in original packaging in dry and ventilated areas at temperatures between +5°C and +25°C. Do not freeze!

These instructions are based on our best experience. However, due to the wide variety of users and application techniques, we cannot guarantee results in every individual case.

