



## Technical Data Sheet

Appearance	Matt
Composition	Siloxane resin, pigments
BROOKFIELD viscosity	500 CPS
Water vapour permeability	High
Alkali resistance	Resistant
Dry solids	15%



## RUSTIK

Rustik-a is a decorative transparent water-based paint for exterior and interior use, based on specific siloxane resins. It breathes and is resistant to UV rays.

### **Substrate preparation:**

When the wall or ceiling is ready for painting, start by applying TIFFANY white, diluted with 40-50% water. After 8 hours, when TIFFANY is dry, apply coloured Decorativ Primer crosswise with a brush. Required applications: 1. Decorativ Primer is produced in three different textures: coarse, medium and fine. This provides the optimum base for applying Rustic-a.

### **Painting Rustik:**

After 8 to 12 hours, when the Decorativ Primer is dry, start applying Rustik. For applying Rustik use a brush, sponge, cloth, decorative roller or decorative glove; everything depends on the application technique and the desired final effect. Consumption: 24 to 28 m<sup>2</sup>.

### **Drying time:**

3 to 4 hours to dust dry; through-drying: 12 to 16 hours. Maximum wash resistance is reached after 48 hours.

Application temperature: +5 to +35°C. Maximum relative ambient humidity: 80%. Wash tools with water after work. Dirty water must not be poured into the drain. Store in the original packaging in dry and ventilated rooms at a temperature between +5°C and +25°C. Do not freeze!