

## SOFT VARNISH – TRANSPARENT

### APPEARANCE:

Transparent finish

### COMPOSITION:

Acrylic-based coating with additives

### DESCRIPTION:

Soft transparent varnish is a water-based coating intended for the protection and enhancement of wood surfaces. It preserves the natural appearance of wood while providing a soft, elegant finish.

It is suitable for interior and exterior use, offering protection against moisture, UV rays, and general wear.

### SURFACE PREPARATION:

The surface must be clean, dry, sanded, and free from dust, grease, and previous coatings.

### APPLICATION:

Apply with a brush, roller, or spray. Stir well before use. Dilute with water up to 10% if needed.

Apply in 2–3 coats with 3–4 hours between applications.

### DRYING TIME:

Touch dry: 2–4 hours

Fully dry: 8–12 hours depending on temperature and humidity

### APPLICATION CONDITIONS:

Temperature: +5°C to +35°C

Relative humidity: max. 80%

Clean tools with water after use.

### STORAGE:

Store in original packaging in dry and ventilated spaces between +5°C and +25°C. Protect from freezing.

### ADVANTAGES:

- Preserves natural wood look
- Soft, elegant finish
- Fast drying
- Water-based and eco-friendly

- Low odor
- Easy application

CONSUMPTION:

Approx. 10–14 m<sup>2</sup> per liter per coat