

SOFT VARNISH – TRANSPARENT

APPEARANCE:

Transparent

COMPOSITION:

Acrylic-based coating with additives, without fillers

DESCRIPTION:

Soft transparent varnish is a water-based coating designed for protecting wood while preserving its natural appearance. It penetrates the surface and enhances the structure of the wood, leaving a soft and elegant finish.

It is suitable for both interior and exterior use. It protects wood against weather conditions, UV rays, moisture, and aging.

Compared to solvent-based coatings, this product is more environmentally friendly, dries faster, and has a mild odor.

SURFACE PREPARATION:

Wood must be dry (max. 20% moisture), sanded, degreased, and dust-free. Edges should be rounded and surfaces properly prepared so water does not accumulate.

For new wood, three coats are recommended.

APPLICATION:

Apply with a brush, roller, or spray. Can be diluted with water up to 10%.

Apply in 2–3 coats with 3–4 hours between coats.

DRYING TIME:

Surface dry: 3–4 hours

Fully dry: 6–12 hours depending on temperature and wood moisture

APPLICATION CONDITIONS:

Temperature: +5°C to +35°C

Relative humidity: max. 80%

Must not freeze

Clean tools with water after use.

STORAGE:

Store in original packaging in dry and ventilated areas between +5°C and +25°C.

ADVANTAGES:

- Preserves natural wood appearance
- Deep penetration
- Water repellent
- UV resistant
- Fast drying
- Low odor
- Environmentally friendly

CONSUMPTION:

16–20 m² per liter per coat

DILUTION:

Up to 10% with water