

TECHNICAL DATA SHEET

Appearance: Matte, fine structure

Composition: Acrylic resin, PU fillers, pigments, additives

Brookfield Viscosity: 8,000 CPS

Water Vapor Permeability: Good

Alkali Resistance: Resistant

Dry Matter: 42%

UV Stability: Good

THUNDER

Thunder is a water-based acrylic decorative paint with PU spheres and pearlescent or pastel pigments, creating a unique decorative appearance. Thanks to its easy application, Thunder enables the creation of a distinctive three-dimensional effect and a stylish ambiance. It is a high-quality product, vapor permeable, UV stable, and washable. The Thunder effect can be applied to various surfaces such as concrete, plastered walls, wood, gypsum boards, and other properly prepared substrates.

Usage: Exterior / Interior

Surface Preparation:

When the wall is prepared for painting and free of defects such as cracks or holes, begin by applying Diffany paint as a base. The darker the base, the more pronounced the pearlescent effect. For pastel pigments, use white Diffany as a primer.

Application:

Thunder is applied using two decorative brushes S.801 simultaneously in one coat for metallic or pearlescent pigments. For pastel pigments, usually one brush is used. If applied in two coats, the second coat should be diluted with 20–30% water. Interval between coats: 3 to 4 hours.

Drying time: 6 to 12 hours depending on temperature and humidity.

Application temperature: +5°C to +35°C. Do not freeze!

Packaging: 0.75 L – 2.5 L

Consumption: 8–10 m²/L

Dilution: water 20–30%

These instructions are based on our best experience. However, due to the wide variety of users and application techniques, we cannot guarantee results in every individual case.

