

TECHNICAL DATA SHEET

TRAVERTINE

Travertine decorative plaster is a thick-layer compound for leveling interior and exterior wall surfaces with a decorative effect. It is made from natural quartz, carbonate fillers, mineral binders and high-quality additives.

Usage:

Suitable for leveling interior and exterior wall surfaces and facades with a thickness up to 5 mm in one layer. It can be applied in layers up to 10 mm in multiple applications. It is suitable as a base for decorative techniques such as concrete, natural stone, marble and smooth surfaces.

Technical Data:

Grain size: 0.17 mm

Color: white

Density: approx. 1100 kg/m³

Water required: approx. 4.8–5 L per 16 kg

Application temperature: +5°C to +25°C

Consumption: approx. 2–3 kg/m²

Working time: approx. 3 hours at 20°C

Vapor permeability: 12.9

Water absorption: 18.57%

Compressive strength: 6.7 MPa

Application:

Mix with water to obtain a homogeneous paste. Let it rest for 10 minutes and remix. Apply with a trowel. The surface must be clean and primed with acrylic emulsion if needed. Optimal sanding time is after approx. 12 hours for each mm thickness.

Storage:

Store in closed packaging in dry ventilated areas. Shelf life: at least 24 months.

Packaging:

16 kg