Blik d.o.o.
barve, laki & zaščitni premazi

BLIK d.o.o., Ulica Jožeta Jame 14, 1000 Ljubljana, Slovenia / EU
phone: +386 (0) 1 518 71 75, fax: +386 (0) 1 518 71 76, e-mail: blik.doo@amis.net, http://www.blik.si

Technical Data Sheet



Appearance	Gloss
Composition	Mixture of acrylic and vinyl resins, pigments and fillers
Brookfield Viscosity	12,000 CPS
Water Vapor Permeability	Low
Alkali Resistance	Resistant
Dry Matter	30%

DAMARA

Damara is a water-based acrylic paint for interior and exterior use, based on special metallic pigments that create a 3D effect. It dries quickly and is resistant to weather conditions. With Damara, an extremely washable surface can be achieved.

Surface preparation:

If the wall or ceiling is prepared for painting and without defects such as cracks or holes, begin with one coat of DIFFANY diluted with 40–50% water. After 8 hours, when the DIFFANY base is dry, start applying DAMARA. Use a spray gun or roller. The first coat dries in approximately 3 hours, after which the second coat can be applied. A maximum of 3 coats is required in most cases. DAMARA is diluted with water up to a maximum of 20%.

Application:

Three application methods are shown in the catalog: 1. Roller application: two to a maximum of three coats depending on the surface and preparation. 2. Brush effect: one coat with a roller, second coat applied crosswise with a brush. 3. Decorative effect: two coats of DAMARA in any shade, third coat of GOLD DAMARA applied with a decorative cloth or roller.

Consumption: 8–12 m²

Drying: 8 hours for a dry and washable surface.

Application temperature: +10°C to +35°C. Relative humidity max. 75%. Clean tools with water after use. Do not pour contaminated water into drains.

Storage: Store in dry and ventilated areas at temperatures between +5°C and +25°C. Do not freeze!

These instructions are based on our best experience. However, due to the wide variety of users and application techniques, we cannot guarantee results in every individual case.